

AC INDUCTION MOTOR DATA SHEET

Model No.or RFQ No.		Item No.		Rev. No. [0]	
Project Name		Project No.		Quantity sets	
GENERAL SPECIFICATION			PERFORMANCE DATA		
Frame Size	132S		Rated Output	3.7 kW 5 HP	
Type	HS		Number of Poles	6	
Enclosure(Protection)	Totally Enclosed (IP55)		Rotor Type	Squirrel Cage	
Method of Cooling	IC411(FC)		Starting Method*	☒ D.O.L ☐ Y- Δ	
Rated Frequency	60 Hz		Rated Voltage	440 V	380 V 220 V
Number of Phases	3		Current	Full Load	7.5 A 8.7 A 15.1 A
Insulation Class	☒ F ☐ B ☐ H		Locked-rotor**	600 %	600 % 600 %
Temp. Rise at full load (by resistance method)			Efficiency		
at 1.0 S.F 80 deg. C			50% Load	86.8 %	
Motor Location	☒ Indoor ☐ Outdoor		75% Load	87.9 %	
Altitude	Less than 1000 meter		100% Load	87.5 %	
Relative Humidity	Less than 80 %		Power Factor(p.u)		
Ambient Temp.	40 deg. C (Max.)		50% Load	0.551	
Duty Type	Continuos (S1)		75% Load	0.676	
Service Factor	1.15		100% Load	0.735	
Mounting	☒ B3 ☐ B5 ☐ V1 ☐ B3/B5		Speed at Full Load	1165 r.p.m	
Bearing	Type	Anti-Friction	Torque		
	DE/N-DE	6208ZZC3 / 6208ZZC3	Full Load	3.1 kg·m	
	Lubricant	Grease(Polyrex-EM)	Locked-rotor**	180 %	
External Thrust	Not applicable		Breakdown**	220 %	
Coupling Method	☒ Direct ☐ V-Belt		Moment of Inertia (J)		
Shaft Extension	☒ Single ☐ Double		Load(Max.)	7.750 kg·m²	
Terminal Box	Main	☐ Steel ☒ Cast Iron	Motor	0.040 kg·m²	
	Aux.	☐ Yes ☒ No	Sound Pressure Level (No-load & mean value at 1m from motor)	62 dB(A)	
	Location	Refer to Outline Drawing	Vibration	1.6 mm/sec (r.m.s)	
Application			Permissible number of consecutive starts	Cold	3 times
Area classification	Non-Hazardous		Hot	2 times	
Type of Ex-Protection	Not applicable		Paint	Munsell No.	4.0PB5.4/5.5(VL-451)
Applicable Standard	KS,IEC,NEMA MG1 Part30(Vpeak)		SUBMITTAL DRAWING		
ACCESSORIES			Outline Dimension Drawing \ Motor Weight(Approx.)		
			B3	227B2000AB03	67 kg
			B5		kg
			V1		kg
			B3/B5		kg
			Main T-Box Ass'y 227B8004CB		
SPARE PARTS			REMARK High Efficiency		
			* For use on PWM VFD 10:1VT, 3:1CT@1.0S.F&F Temp. rise		
			Date	DSND	CHKD
			2011-04-14	W.H.BACK	S. J. RA
					CHKD
					APPD
					J. H. KIM

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be maker standard, if not mentioned.

* In case of Inverter-Fed Motor, performance data is based on sine wave tests.


** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.

HHI W230-131-1 * In case of Inverter or V.V.V.F Motor:Performance data is based on sine wave tests. A4(210mm X 297mm)


Type	:	HS
Full Load Torque	:	3.1 Kg.m
Motor moment of Inertia (J)	:	0.040 Kg.m ²
Load moment of Inertia (J)	:	7.750 Kg.m ²


3.7 kW		6 P		60 Hz	
Speed at Full Load :				1165 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	7.5A	8.7A	15.1A		

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE






NOTE


1.TOLERANCE :

CENTER HEIGHT	132	$\begin{smallmatrix} 0 \\ -0.5 \end{smallmatrix}$
BASE HOLES	$\phi 12$	$\begin{smallmatrix} +0.43 \\ 0 \end{smallmatrix}$
SHAFT DIAMETER	$\phi 38$	$\begin{smallmatrix} +0.018 \\ +0.002 \end{smallmatrix}$
KEYWAY WIDTH	10	$\begin{smallmatrix} 0 \\ -0.036 \end{smallmatrix}$
KEYWAY DEPTH	5	$\begin{smallmatrix} +0.2 \\ 0 \end{smallmatrix}$



CAST IRON CONDUIT BOX

APPD BY	J. H. KIM	UNIT	mm	SUBJECT	KS 132S	CAD PROJ \ FILE
CHKD BY	Y. S. KIM	SCALE	1/6			XSDNKS\B2000AB03
CHKD BY	S. H. KO	PROJEC'N	3rd Angle	TITLE OUTLINE		
DSND BY	I. K. KIM	DATE	2001.10.26			
HYUNDAI HEAVY INDUSTRIES CO., LTD. Electro-Electric System Division				REF. NO	B2000AB03	Sheet No. of
				DWG NO	227B2000AB03	Revision No. 0



QTY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APPD BY	UNIT	MM	SUBJECT	IEC 100 - 132	CAD PROJ. FILE		
CHKD BY	SCALE	1/1	PROJECT	3-4 (3rd Angle)	XSMOUT\7B8004CB		
CHKD BY	DATE	2005.10.19.	TITLE	TERMINAL BOX ASS'Y			
DSND BY	J. S. JEONG		REF. NO.	7B8004CB	Sheet No. of		
			DWG NO.	227B8004CB	Revision No. 0		