

AC INDUCTION MOTOR DATA SHEET

Model No.or RFQ No.		Item No.		Rev. No. [0]			
Project Name		Project No.		Quantity sets			
GENERAL SPECIFICATION			PERFORMANCE DATA				
Frame Size	180M		Rated Output	22 kW 30 HP			
Type	HL-XP		Number of Poles	2			
Enclosure(Protection)	Explosion Proof (IP55)		Rotor Type	Squirrel Cage			
Method of Cooling	IC411(FC)		Starting Method*	☒ D.O.L ☐ Y- Δ			
Rated Frequency	60 Hz		Rated Voltage	440 V	380 V 220 V		
Number of Phases	3		Current	Full Load 34.9 A	40.4 A 69.7 A		
Insulation Class	☒ F ☐ B ☐ H		Locked-rotor**	650 %	650 % 650 %		
Temp. Rise at full load (by resistance method)			Efficiency				
at 1.0 S.F 80 deg. C			50% Load	90.5 %			
Motor Location	☒ Indoor ☐ Outdoor		75% Load	91.5 %			
Altitude	Less than 1000 meter		100% Load	91.0 %			
Relative Humidity	Less than 80 %		Power Factor(p.u)				
Ambient Temp.	40 deg. C (Max.)		50% Load	0.865			
Duty Type	Continuos (S1)		75% Load	0.900			
Service Factor	1.00		100% Load	0.910			
Mounting	☒ B3 ☐ B5 ☐ V1 ☐ B3/B5		Speed at Full Load	3540 r.p.m			
Bearing	Type	Anti-Friction	Torque				
	DE/N-DE	6310ZZC3 / 6310ZZC3	Full Load	6.1 kg·m			
	Lubricant	Grease(Polyrex-EM)	Locked-rotor**	180 %			
External Thrust	Not applicable		Breakdown**	220 %			
Coupling Method	☒ Direct ☐ V-Belt		Moment of Inertia (J)				
Shaft Extension	☒ Single ☐ Double		Load(Max.)	2.850 kg·m²			
Terminal Box	Main	☐ Steel ☒ Cast Iron	Motor	0.080 kg·m²			
	Aux.	☐ Yes ☒ No	Sound Pressure Level (No-load & mean value at 1m from motor)	86 dB(A)			
	Location	Refer to Outline Drawing	Vibration	2.2 mm/sec (r.m.s)			
Application			Permissible number of consecutive starts	Cold 3 times	Hot 2 times		
Area classification	Hazardous		Paint	Munsell No.	4.0PB5.4/5.5(VL-451)		
Type of Ex-Protection	Ex d IIB T4		SUBMITTAL DRAWING				
Applicable Standard	KS,IEC		Outline Dimension Drawing \ Motor Weight(Approx.)				
ACCESSORIES			B3	227B2002AA07	199 kg		
			B5		kg		
			V1		kg		
			B3/B5		0 kg		
			Main T-Box Ass'y	227B1470LB			
SPARE PARTS			REMARK				
			High Efficiency				
			Date	DSND	CHKD	CHKD	APPD
			2011-04-14	W.H.BACK	S. J. RA	O. J. KIM	J. H. KIM

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be maker standard, if not mentioned.

* In case of Inverter-Fed Motor, performance data is based on sine wave tests.


** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.

HHI W230-131-1 * In case of Inverter or V.V.V.F Motor:Performance data is based on sine wave tests. A4(210mm X 297mm)


Type	:	HL-XP
Full Load Torque :	6.1	Kg.m
Motor moment of Inertia (J) :	0.080	Kg.m ²
Load moment of Inertia (J) :	2.850	Kg.m ²

22 kW		2 P		60 Hz	
Speed at Full Load :				3540 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	34.9A	40.4A	69.7A		


SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE




Exd II




NOTE

1.TOLERANCE :

CENTER HEIGHT	180	$\begin{smallmatrix} 0 \\ -0.5 \end{smallmatrix}$
BASE HOLES	$\phi 15$	$\begin{smallmatrix} +0.43 \\ 0 \end{smallmatrix}$
SHAFT DIAMETER	$\phi 48$	$\begin{smallmatrix} +0.018 \\ +0.002 \end{smallmatrix}$
KEYWAY WIDTH	14	$\begin{smallmatrix} 0 \\ -0.043 \end{smallmatrix}$
KEYWAY DEPTH	5.5	$\begin{smallmatrix} +0.2 \\ 0 \end{smallmatrix}$



APPD BY	Y. S. KIM	UNIT	mm	SUBJECT	KS 180M	CAD PROJ \ FILE
CHKD BY	K. S. LEE	SCALE	1/8.5			XSDNKS\B2002AA07
CHKD BY	-----	PROJEC'N	3rd Angle	TITLE	OUTLINE	
DSND BY	I. K. KIM	DATE	2008.10.22			
HYUNDAI HEAVY INDUSTRIES CO., LTD. Electro-Electric System Division				REF. NO	B2002AA07	Sheet No. of
				DWG NO	227B2002AA07	Revision No. 0

[illegible]