

Customer :
Project Name :
Project No. :
Revision No. :

SPECIFICATION for INDUCTION MOTOR



Contents

1 . Data Sheet of AC Induction Motor	- 1Sheets
2 . Speed-Torque & Current Curve	- 1Sheets
3 . Outline Dimension Drawing	- 1Sheets
4 . Main Terminal Box Drawing	- 1Sheets

		AC INDUCTION MOTOR DATA SHEET											
Model No.or RFQ No.		4606KSTD40SSDS1STFE3B51DL0SDS		Item No.		Rev. No.		[]					
Project Name				Project No.		Quantity							
GENERAL SPECIFICATION				PERFORMANCE DATA									
Frame Size		132M		Rated Output		5.5 kW		8 HP					
Type		HKP-5.5/6		Number of Poles		6							
Enclosure(Protection)		Totally Enclosed (IP55)		Rotor Type		Squirrel Cage							
Method of Cooling		IC411(FC)		Starting Method*		☒ D.O.L ☐ Y-Δ							
Rated Frequency		60 Hz		Rated Voltage		460 V							
Number of Phases		3		Current		Full Load		10.4 A					
Insulation Class		☒ F ☐ B ☐ H				Locked-rotor**		750 %					
Temp. Rise at full load (by resistance method)				Efficiency									
at 1.0 S.F		80 deg. C				50% Load		91.0 %					
Motor Location		☒ Indoor ☐ Outdoor				75% Load		91.6 %					
Altitude		Less than 1000				100% Load		91.0 %					
Relative Humidity		Less than 80 %		Power Factor(p.u)									
Ambient Temp.		40 deg. C (Max.)				50% Load		0.573					
Duty Type		Continuous(S1)				75% Load		0.681					
Service Factor		1.15				100% Load		0.731					
Mounting		☐ B3 ☒ B5 ☐ V1 ☐ B3/B5		Speed at Full Load		1175 r.p.m							
Bearing	Type	Anti-Friction		Torque									
	DE/N-DE	6308ZZC3 / 6308ZZC3				Full Load		4.6 kg·m					
	Lubricant	Grease(Polyrex-EM)				Locked-rotor**		170 %					
External Thrust		Not applicable				Breakdown**		250 %					
Coupling Method		☒ Direct ☐ V-Belt		Moment of Inertia (J)									
Shaft Extension		☒ Single ☐ Double				Load(Max.)		13.000 kg·m²					
Terminal Box	Main	☐ Steel ☒ Cast Iron				Motor		0.052 kg·m²					
	Aux.	☐ Yes ☒ No		Sound Pressure Level (No-load & mean value at 1m from motor)									
	Location	Refer to Outline Drawing				62 dB(A)							
Application				Vibration		1.6 mm/sec (r.m.s)							
Area classification		Not applicable		Permissible number of consecutive starts		Cold		3 times					
Type of Ex-Protection		Non-Hazardous				Hot		2 times					
Applicable Standard		KS, IEC, NEMA MG1 Part30(Vpeak)		Paint		Munsell No.		4.4PB5.5/5.6(VL-451)					
ACCESSORIES				SUBMITTAL DRAWING									
				Outline Dimension Drawing		\		Motor Weight(Approx.)					
				B5		LM-T0133B5PL001		79 kg					
				Main T-Box Ass'y		3M-148549							
				REMARK									
				*.Premium Efficiency(IE3) *.For use on PWM VFD 10:1VT,3:1CT@1.0S.F&F Temp.rise									
SPARE PARTS													
				Date		DSND		CHKD		CHKD		APPD	
				2018-04-25		R.G. KIM		-		O.J. KIM		S.K. HAN	

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be maker standard, if not mentioned.

* In case of Inverter-Fed Motor, performance data is based on sine wave tests.

** The data are based on rated voltage & frequency, and data are expressed as a percentage of full load value.

HEES W230-131-1

* In case of Inverter or V.V.V.F Motor:Performance data is based on sine wave tests.

A4(210mm X 297mm)

Type : HKP-5.5/6

Full Load Torque : 4.6 kg.m

Motor moment of Inertia (J) : 0.052 kg.m²

Load moment of Inertia (J) : 13.000 kg.m²

5.5 kW

6 P


60 Hz

Speed at Full Load : 1175 RPM


Rated Voltage 460V


Full Load Current 10.4A

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE








본 도면은 현대일렉트릭(주) 제산이미타
허가없이 복사할 수 없음 (저작권의)

THIS DRAWING IS PROPRIETARY TO HYUNDAI ELECTRIC. NO PART OF THIS DRAWING
MAYBE REPRODUCED WITHOUT THE PERMISSION OF HYUNDAI ELECTRIC.



SEC. "A"—"A"

▽	50S
▽▽	12.5S
▽▽▽	3.2S
▽▽▽▽	0.4S

REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY

일반가공공차		일반계공공차	
1-4	±0.1	6-30	±0.5
4-18	±0.2	30-120	±0.8
18-63	±0.3	120-315	±1.2
63-250	±0.5	315-1000	±2.0
250-	±0.8	1000-	±3.0

Q'TY		DESCRIPTION		MATERIAL	DIMENSION		WEIGHT	PART NO.	REMARK	NO.	
APPD	BY	S.K.HAN	UNIT	mm	SUBJECT	FR.100~132 (CAST IRON)				DWG SIZE	
CHKD	BY	S.Y.KIM	SCALE	1/2	TITLE Terminal Box Arrangement						A3 (1:2)
CHKD	BY	R.G.KIM	PROJEC'N	3각법 (3rd Angle)							
DSND	BY	H.K.LEE	DATE	2011-10-26							
					REF. NO	227B8004CB		Sheet No. of			
					DWG NO	3M-148549		Revision No. 2			