


| | | | | | | | | |
|---|-----------|---|--|--|----------|--|----------|---------|
|  | | AC INDUCTION MOTOR DATA SHEET | | | | | | |
| Model No.or RFQ No. | | Item No. | | Rev. No. | | [0] | | |
| Project Name | | Project No. | | Quantity | | set | | |
| GENERAL SPECIFICATION | | | | PERFORMANCE DATA | | | | |
| Frame Size | | 132S | | Rated Output | | 3.7 kW 5 HP | | |
| Type | | HLP-3.7/6 | | Number of Poles | | 6 | | |
| Enclosure(Protection) | | Totally Enclosed (IP55) | | Rotor Type | | Squirrel Cage | | |
| Method of Cooling | | IC411(FC) | | Starting Method* | | <input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-Δ | | |
| Rated Frequency | | 60 Hz | | Rated Voltage | | 440 V 380 V 220 V | | |
| Number of Phases | | 3 | | Current | | Full Load 7.7 A 9.0 A 15.5 A | | |
| Insulation Class | | <input checked="" type="checkbox"/> F <input type="checkbox"/> B <input type="checkbox"/> H | | Locked-rotor** | | 720 % 720 % 720 % | | |
| Temp. Rise at full load (by resistance method) | | | | Efficiency | | | | |
| at 1.0 S.F | | 80 °C | | 50% Load | | 89.2 % | | |
| Motor Location | | <input checked="" type="checkbox"/> Indoor <input type="checkbox"/> Outdoor | | 75% Load | | 90.0 % | | |
| Altitude | | Less than 1000m | | 100% Load | | 89.5 % | | |
| Relative Humidity | | Less than 80 % | | Power Factor(p.u) | | | | |
| Ambient Temp. | | 40 °C MAX. | | 50% Load | | 0.520 | | |
| Duty Type | | Continuous(S1) | | 75% Load | | 0.630 | | |
| Service Factor | | 1.15 | | 100% Load | | 0.700 | | |
| Mounting | | <input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3/B5 | | Speed at Full Load | | 1170 r.p.m | | |
| Bearing | Type | Anti-Friction | | Torque | | | | |
| | DE/N-DE | 6208ZZC3 / 6208ZZC3 | | Full Load | | 3.1 kg.m | | |
| | Lubricant | Grease(Polyrex-EM) | | Locked-rotor** | | 170 % | | |
| External Thrust | | Not applicable | | Breakdown** | | 220 % | | |
| Coupling Method | | <input checked="" type="checkbox"/> Direct <input type="checkbox"/> V-Belt | | Moment of Inertia (J) | | | | |
| Shaft Extension | | <input checked="" type="checkbox"/> Single <input type="checkbox"/> Double | | Load(Max.) | | 7.70042735 kg·m² | | |
| Terminal Box | Main | <input type="checkbox"/> Steel <input checked="" type="checkbox"/> Cast Iron | | Motor | | 0.052 kg·m² | | |
| | Aux. | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | Sound Pressure Level (No-load & mean value at 1m from motor) | | | | |
| | Location | Refer to Outline Drawing | | | | 63 dB(A) | | |
| Application | | | | Vibration | | 1.6 mm/sec(r.m.s) | | |
| Area classification | | Non-Hazardous | | Permissible number of consecutive starts | | Cold 3 times Hot 2 times | | |
| Type of Ex-Protection | | Not applicable | | Paint | | Munsell No. Panton279C | | |
| Applicable Standard | | KS, IEC, NEMA MG1 Part30(Vpeak) | | | | | | |
| ACCESSORIES | | | | SUBMITTAL DRAWING | | | | |
| | | | | Outline Dimension Drawing \ | | Motor Weight(Approx.) | | |
| | | | | B3 | | LM-T0131B3PLV01 | 68 kg | |
| | | | | B5 | | | kg | |
| | | | | V1 | | | kg | |
| | | | | B3/B5 | | | kg | |
| | | | | Main T-Box Ass'y | | 3M-148549 | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | REMARK | | | | |
| | | | | *.Premium Efficiency(IE3) | | | | |
| | | | | *.For use on PWM VFD 10:1VT,3:1CT@1.0S.F&F Temp.rise | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| SPARE PARTS | | | | | | | | |
| | | | | Date | DSND | CHKD | CHKD | APPD |
| | | | | 2018-11-23 | R.G. KIM | --- | O.J. KIM | S.K.HAN |
| Note: Others not mentioned in this data sheet shall be in accordance with maker standard. Above technical data are only design values and shall be guaranteed with tolerance of applicable standard. Inspection and performance test shall be maker standard, if not mentioned. * In case of Inverter-Fed Motor, performance data is based on sine wave tests. ** The data are based on rated voltage & frequency, and data are expressed as a percentage of full load value. | | | | Made in Vietnam | | | | |
| HEES W230-131-1 * In case of Inverter or V.V.V.F Motor:Performance data is based on sine wave tests. | | | | A4(210mm X 297mm) | | | | |

본 도면은 현대일렉트릭(주) 재산이므로
허가없이 복사할 수 없음 (취급주의)

THIS DRAWING IS PROPRIETARY TO HYUNDAI ELECTRIC. NO PART OF THIS DRAWING
MAYBE REPRODUCED WITHOUT THE PERMISSION OF HYUNDAI ELECTRIC.

